




GB5M700 RFID Inlay Product Spec Sheet

Applications

Apparel - Baggage - Denim - Footwear - Polybags - Retail

Key Benefits


- ✓ Pre-Serialization of 96 bit EPC
- ✓ Excellent Performance
- ✓ Supply Chain Management
- ✓ Robust Performance on Variety of Materials
- ✓ Inventory Management




Technical Features

Antenna Size / Web Width	42 X 24 mm [1.61 X 1.02 in] / 65 mm [2.56 in]
Integrated Circuit (IC) Type	Impinj M700
Operating Frequency	860 - 960MHz
RF Communications Protocol	ISO/IEC 18000-63 and EPC Global Class 1 Gen2
ARC Approved Spec	N, Q, G, F, W2, W5, W6
Chip Memory	M730: 128bits EPC; M750: 96bits EPC
Inlay Substrate Material	PET
IC Features	Autotune Adaptive RF Tuning; Short-Range Mode; FastID High-Speed Reading; Self-Serialization
Read Sensitivity	-24 dBm
Write Sensitivity	-21 dBm
Operating Temperature	-5°C to 60°C / 23°F to 140°F
Operating Humidity	20% - 60% RH

Orientation Read Range (m)



Sensitivity Results from Free Space (dBm)



For more information, please contact us at sml.com/requestinfo.



This product should be tested by the customer / user thoroughly to ensure conformity to any particular requirements. We do not represent that this product is fit for any particular purpose or use. We reserve all rights to modify, supplement, substitute or discontinue product offerings at any time without notice. The information contained herein is for pure guidance but contains no representation concerning the accuracy or correctness of the data.